

### Amendments in the Claims:

This listing of claims will replace all prior versions and listings of claims in the Application:

- 5 1. (Currently Amended) In a system for transporting water through a ditch, an inlet/outlet box comprising:
- a liner section having an entrance end, an exit end, and opposing fins therebetween;
- a locking channel segment monolithically formed substantially adjacent the exit end;
- opposing handle assemblies formed monolithically adjacent the entrance end and the exit
- 10 end; and
- means for anchoring the inlet/outlet box, wherein the anchoring means includes a floor monolithically extending between the opposing fins adjacent the exit end, and a recessed chamber monolithically extending between the opposing fins adjacent the entrance end.
- 15 2. (Currently Amended) In a system for transporting water through a ditch, an inlet/outlet box as recited in claim 1, wherein the liner section is substantially semi-circular in cross-section.
3. (Currently Amended) In a system for transporting water through a ditch, an inlet/outlet box as recited in claim 1, wherein the exit end is substantially semi-circular in cross-section.
- 20 4. (Currently Amended) In a system for transporting water through a ditch, an inlet/outlet box as recited in claim 1, wherein the entrance end is substantially rectangular in cross-section.
5. (Original) In a system for transporting water through a ditch, an inlet/outlet box as recited
- 25 in claim 1, wherein the opposing handle assemblies include one or more holes for slidable engagement with a rod.
6. (Canceled) ~~In a system for transporting water through a ditch, an inlet/outlet box as recited in claim 1, wherein the anchoring means includes a floor monolithically extending~~

~~between the opposing fins adjacent the exit end, and a recessed chamber monolithically extending between the opposing fins adjacent the entrance end.~~

7. (Withdrawn) In a system for transporting water through a ditch, a splitter section comprising:

a liner section having a leading end, a following end, and a substantially corrugated first chute therebetween,

wherein the substantially corrugated first chute is formed with a passage;

a first locking channel segment monolithically formed adjacent the following end of the liner section;

a second locking channel segment monolithically formed adjacent the leading end of the liner section; and

a drain monolithically mounted adjacent the substantially semi-circular passage.

8. (Withdrawn) In a system for transporting water through a ditch, a splitter section as recited in claim 7, wherein the liner section is substantially semi-circular.

9. (Withdrawn) In a system for transporting water through a ditch, a splitter section as recited in claim 8, wherein the chute is formed with opposing edges.

10. (Withdrawn) In a system for transporting water through a ditch, a splitter section as recited in claim 9, wherein the substantially semi-circular passage is formed through at least one of the opposing edges.

11. (Withdrawn) In a system for transporting water through a ditch, a splitter section as recited in claim 10, wherein the drain is formed to include a locking channel segment for detachable connecting the drain to another locking channel segment.

12. (Withdrawn) In a system for transporting water through a ditch, a diversion section comprising:

a liner section formed with a trailing end, an advance end, and a substantially corrugated second chute;

an opening through the substantially corrugated second chute; and

a hollow cylinder member mounted over the opening,

5                    wherein the hollow cylinder member extends in a direction opposite the longitudinal axis through the center of the substantially corrugated second chute.

13.    (Withdrawn) In a system for transporting water through a ditch, a diversion section as recited in claim 12, wherein the opening and hollow cylinder member are formed monolithically  
10    in the substantially corrugated second chute.

14.    (Withdrawn) In a system for transporting water through a ditch, a diversion section as recited in claim 12, further comprising one or more handles adjacent the trailing end and advance end of the substantially corrugated second chute.

15.    (Withdrawn) In a system for transporting water through a ditch, a diversion section as recited in claim 12, further comprising a first locking channel segment monolithically formed adjacent the trailing end of the liner section.

16.    (Withdrawn) In a system for transporting water through a ditch, a diversion section as recited in claim 12, further comprising a second locking channel segment monolithically formed adjacent the advance end of the liner section.

17.    (Withdrawn) In a system for transporting water through a ditch, an adaptor, comprising:  
25           a liner section having a forward end and a back end; and  
          at least three locking channel segments monolithically formed in the liner section between the forward end and the back end of the liner section.

18.    (Withdrawn) In a system for transporting water through a ditch, an adaptor as recited in  
30    claim 17, wherein the at least three locking channel segments include at least two compatible

locking channel segments monolithically formed adjacent the forward end and the back end of the liner section, and an incompatible locking channel segment therebetween.

- 5      19.      (Withdrawn) In a system for transporting water through a ditch, an adaptor as recited in claim 18, further comprising one or more handles monolithically mounted on the at least two similar locking channel segments.

10